

# STCS - VMir

Ref: 14-01-0022

**mecalbi**  
ENHANCE INNOVATING


## Shrinking Tube Control System

The STCS-VMir is a heat shrink system, based on infrared technology. It's designed for workbench applications and can process several parts at the same time.


The same machine can be used on several applications, since it's equipped with a fast exchangeable shrinking chamber system.

The chambers are designed according with the application specifications, making them ideal for special applications.


The system was designed to ensure optimal conditions for CAN processing (normal and end splices), but can also be used for any given application.



Fast removable shrinking chamber



Open work area for faster setup time



New and improved interface based on Touchscreen technology, that allows network communication



**Mecalbi**  
Engineering Solutions, Lda

**Headquarters:** Rua Dr. Alfredo da Silva, Lt 92 R/C,  
6000-210, Castelo Branco, Portugal

**Mecalbi Operations Center:**  
Zona Industrial de Castelo Branco,  
Rua J, Lt N14, Módulo A,  
6000-459, Castelo Branco, Portugal

**Tel. / Fax.** +351 272 325 264  
**Email.** [comercial@mecalbi.com](mailto:comercial@mecalbi.com)  
**Youtube Channel.** [www.youtube.com/mecalbi](http://www.youtube.com/mecalbi)  
**Mod:** 03.02.023-E | **Ref:** 027615-80-002-R01

Copyright © 2015 Mecalbi. All rights reserved. All Mecalbi's brands and product names are service marks, trademarks or registered trademarks of Mecalbi Engineering Solutions, Lda. All other marks are the property of their respective owners. Mecalbi reserve the right to make corrections, modifications, enhancements, improvements and other changes without prior notice.

## TECHNICAL CHARACTERISTICS

## WORKING TEMPERATURE

Minimum	250 [°C]
Maximum	550 [°C]

## DIMENSIONS

Length	490 [mm]
Width	445 [mm]
Height	308 [mm]
Weight	29 [kg]

## POWER SUPPLY/CONSUMPTION

Supply	230 [V] @ 50Hz
Standby Consumption	500 mA
Working Consumption	500 mA to 7 A (Max. 1500W)

## PNEUMATIC

Supply	Quick Hold Socket ø8 [mm]
Supply Pressure	Min: 5bar; Max: 8bar; Rec: 6bar

## CONNECTIONS

Barcode Reader	USB
Temperature Sensor	Type K Thermocouple
Power Line	1 IEC Socket
Programming	Touchscreen
Interface	Touchscreen, Buzzer and LED

## SHRINKING CHAMBER

Shrinking Chamber [Max]	120 x 120 [mm]
Shrinking Tube Diameter [Max]	20 [mm]

## OPERATION

The open work area significantly reduces the setup time of the assemblies.

The STCS-VMir consists in two infrared ovens that come to the front and shrink the assemblies both from top and bottom, improving the temperature's balancing all around the chamber.

When the process finishes, the ovens return to its original position and the cooling system acts refrigerating the work area.

For each machine it's possible to use an indefinite number of shrinking chambers.

- ▲ Adjustable parameters: process temperature, shrinking time, cooling time, etc;
- ▲ Easy and fast replaceable shrinking chamber;
- ▲ Two different operating modes: M1 with temperature and shrinking time control; and M2 mode with pre-programmed references (999 in total);
- ▲ Pre-programming of references using a PC with STCS-RCT software (reads Excel™ files) or a USB stick;
- ▲ Automatic selection of references using a barcode reader or manually on the Touchscreen;
- ▲ Easy firmware upgrade using a USB stick;
- ▲ Use of labels for each shrinking time inside a reference;
- ▲ Built-in cooling system;
- ▲ Manual and automatic calibration;
- ▲ Programming mode password protected;
- ▲ Special maintenance mode for hardware debug;
- ▲ External temperature probe connection for temperature reading and offset adjustment;
- ▲ Automatic cool-down cycle to extend the life of components;
- ▲ Partial and global cycle counter;
- ▲ Working time counter;
- ▲ Network communication;
- ▲ Interchangeable system language including: English, Portuguese, French and Spanish (others on demand).

## OPTIONS

## Custom shrinking chamber

Ref: 06-01-0222

